# FLOS

■ F1060019 Yellow

Bellhop Table
Designed by Edward Barber and Jay Osgerby, 2018

2.5W - 151lm - 2700K

Rechargeable direct light table lighting device. Base and dome in coloured PC. Diffuser in Opaline injection moulded photo-engraved PC. 24-hours' autonomy, charging via Micro-USB-C. Push-button switch positioned on the base provides the 4-step dimmer function. Battery status indicator positioned under the base. USB-C charging cable included, useful length 120cm. USB battery charging on plug with interchangeable plugs.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

ø 125 mm
210 mm

Main specifications

EAN	8059607001295
Mounting	Table
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Lamp holder	LED Module
Power (W)	2.5
System flux (lm)	151

Physical

Colour	Yellow
Length (mm)	210
Net weight (kg)	1.3
Package volume (m3)	0.01
IP	20

Download

Mounting instructions	↓ PDF
Spare Parts	↓ PDF

Photometric Files

LDT / IES	↓ LDT

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP

RETILAP · 03 · c UL us LISTED · RG 0 IEC 62471 · IP 20

Schematic light drawing

90°   90°
60°   60°
30°   63 cd   30°

Luminous flux luminaire
151 lm

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700

Electrical

|	
Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/5
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 5V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	Yes
Battery type	LI-PO
Charging max power	14
Charging min time	3h - 0% to 100%
Charging socket/connector	USB-C

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class C

Replaceable (LED only) light source by a professional

Replaceable control gear by an end-user

Spare Parts

RF1035109

Power charger with electrical
cable & plugs