Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Desi	ign By Us
-------------------------------------	-----------

Supplier's address: Design By Us, Rentemestervej 43, 2400 Copenhagen NV, DK

Model identifier: Globe Bulb Ø80 - Crown Silver | 3,5W

T۱	/pe	of	lig	ht	SO	urc	e:
•)	, PC	0.	יסיי		30	u. c	C .

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	Yes	Dimmable:	Yes

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consur mode (kWh/10 up to the neare	00 h), rounded	4	Energy efficiency class	E	
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode pow pressed in W	ver (P _{on}), ex-	3,6	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90	
Outer dimen-	Height	120	Spectral power dis-	See image	
sions without	Width	80	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	80	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime-					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	35		
		Chromaticity coordinates (x and y)	0,463 0,420		
Parameters for LED and OLED light sources:					
R9 colour rendering index va	lue 0	Survival factor	1,00		
the lumen maintenance factor	or 0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-		
Claims that an LED light sou replaces a fluorescent lig source without integrated by last of a particular wattage.	ght	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-		

(a)'-': not applicable; (b)'-': not applicable;